

1 Amendments to the Claims:

2       This listing of claims will replace all prior versions, and  
3 listings, of claims in the application using (Original) (Currently  
4 Amended) (New) (Canceled) nomenclature, as recited in the below  
5 listing of claims.

6  
7 1. (Currently Amended) A method of broadcasting from a proximal  
8 cache at a proximal internet protocol address (IPA) a routing item  
9 for indicating an originator storing web content data associated  
10 with a uniform resource locator (URL) of a web server permanently  
11 storing the web content data, the method comprising the steps  
12 of[[,]]:

13       originating URL identifier generating an originating URL  
14 identifier for indicating the URL,

15       originating IPA generating an originating IPA for indicating  
16 the originator,

17       destination IPA generating a destination IPA for indicating a  
18 destination cache,

19       associating the originating IPA and the originating URL as the  
20 routing item, and

21       transmitting the routing item from the proximal cache at the  
22 proximal IPA to the destination cache at a destination IPA.

23  
24  
25  
26  
27  
28 ///

1 2. (Currently Amended) The method of claim 1 further comprising the  
2 steps of[[,]]:

3 distance generating a distance metrics for indicating a web  
4 hop distance of a number of the plurality of cooperative web caches  
5 through which the URL web content data would be communicated from  
6 the from the originator through the plurality of cooperative web  
7 caches to the proximal web cache.

8  
9 3. (Original) The method of claim 2 wherein,

10 the originating URL identifier is a proximal URL identifier,  
11 the originating IPA is the proximal IPA,  
12 the proximal cache stores locally the web content data, and  
13 the metric distance is one indicating that one web hop is  
14 between the destination cache to the proximal cache.

15  
16 4. (Original) The method of claim 2 wherein,

17 the originating URL identifier is a source URL identifier,  
18 the originating IPA is the source IPA indicating an IPA  
19 location of a source distally storing the web content data,  
20 the metric distance is greater than one indicating a number  
21 greater than one of the number of web hops between the destination  
22 cache through the proximal cache to the source distally storing the  
23 web content data.

24  
25  
26  
27  
28 ///

1 5. (Original) The method of claim 4 wherein,

2 the source is a distal web cache distally storing the web  
3 content data, and

4 the source IPA is a distal web cache IPA.

6  
7 6. (Original) The method of claim 4 wherein,

8 the source is the web server distally permanently storing the  
9 web content data, and

10 the source IPA is a web server IPA indicating the IPA location  
11 of the web server.

12  
13 7. (Original) The method of claim 1 wherein,

14 the originating URL identifier is selected from the group  
15 consisting of,

16 an exact URL identifier being an exact URL comprising a  
17 plurality of URL components,

18 a wildcard URL identifier being a wildcard URL comprising a  
19 plurality of URL components a last URL component of which being a  
20 wildcard component, and

21 a coded URL identifier being a coded URL comprising a series  
22 of hashing codes of a decomposed URL being a decomposition of the  
23 URL selected from the group consisting of either an exact URL or a  
24 wildcard URL each of which comprising a series of URL components,  
25 the series of hashing codes being a sequence of hashing codes of  
26 respective URL segments of a respective series of increasingly  
27 concatenated URL components of the series of URL components of the  
28 URL.

1 8. (Currently Amended) A method of broadcasting from a proximal  
2 cache at a proximal internet protocol address (IPA) a routing item  
3 for indicating a distal web cache storing web content data  
4 associated with a uniform resource locator (URL) of a web server  
5 permanently storing the web content data, the proximal web cache is  
6 a first one of a plurality of cooperative web caches, the distal  
7 web caches is a last one of the plurality of cooperative web  
8 caches, the method comprising the steps of[[,]]:

9 URL identifier generating a URL identifier for indicating the  
10 web content data of the URL stored in the distal web cache,

11 proximal IPA generating the proximal IPA for indicating the  
12 location of the proximal cache,

13 destination IPA generating a destination IPA for indicating a  
14 destination cache,

15 distance generating a distance metric for indicating a web hop  
16 distance of any number of the plurality of cooperative web caches  
17 through which the web content data would be communicated from the  
18 distal web cache to the destination web cache,

19 associating the proximal IPA and the URL identifier and the  
20 distance metric as the routing item, and

21 transmitting the routing item from the proximal cache at the  
22 proximal IPA to the destination cache at a destination IPA.

23  
24 9. (Original) The method of claim 8 wherein,

25 the distance metric is greater than one indicating a number  
26 greater than one of the number of web hops between the destination  
27 cache through the proximal cache to the distal web cache storing  
28 the web content data.

1 10. (Original) The method of claim 8 wherein,  
2 the URL identifier is selected from the group consisting of,  
3 an exact URL identifier being an exact URL comprising a  
4 plurality of URL components,  
5 a wildcard URL identifier being a wildcard URL comprising a  
6 plurality of URL components a last URL component of which being a  
7 wildcard component, and  
8 a coded URL identifier being a coded URL comprising a series  
9 of hashing codes of a decomposed URL being a decomposition of the  
10 URL selected from the group consisting of either an exact URL or a  
11 wildcard URL each of which comprising a series of URL components,  
12 the series of hashing codes being a sequence of hashing codes of  
13 respective URL segments of a respective series of increasingly  
14 concatenated URL components of the series of URL components of the  
15 URL.

16  
17  
18 11. (Currently Amended) The method of claim 8 further comprising  
19 the steps of[[,]]:

20 repeating the URL identifier generating step, proximal IPA  
21 generating step, distance generating step, the associating step, a  
22 plurality of times for generating a plurality of routing items each  
23 comprising a URL identifier and a respective distance metric, and  
24 incorporating the plurality of routing items within a protocol  
25 data structure within the routing packet prior to the transmitting  
26 step, the routing protocol packet comprising the URL and a  
27 respective distance metrics and comprising the proximal IPA and the  
28 destination IPA.

1 12. (Currently Amended) A method of broadcasting from a proximal  
2 cache at a proximal internet protocol address (IPA) a routing item  
3 for indicating a distal web cache storing web content data  
4 associated with a uniform resource locator (URL) of a web server  
5 permanently storing the web content data, the proximal web cache is  
6 a first one of a plurality of cooperative web caches, the distal  
7 web caches is a last one of the plurality of cooperative web  
8 caches, the method comprising the steps of[[,]]:

9       storing in a routing table a plurality of URL identifiers  
10       cross referenced to a respective plurality of distance metrics,  
11       URL identifier generating a URL identifier of the plurality of  
12       URL identifiers, the URL identifier for indicating the web content  
13       data of the URL stored in the distal web cache,

14       proximal IPA generating the proximal IPA for indicating the  
15       location of the proximal cache,

16       destination IPA generating a destination IPA for indicating a  
17       destination cache,

18       distance generating a distance metrics by cross referencing  
19       the URL identifier to one of the plurality of URL identifiers and  
20       to a respective one of the plurality of distance metrics for  
21       indicating a web hop distance of any number of the plurality of  
22       cooperative web caches through which the web content data would be  
23       communicated from the distal web cache to the destination web  
24       cache,

25       associating the proximal IPA and the URL and the distance  
26       metrics as the routing item, and

1 transmitting the routing item in a routing packet within a  
2 routing protocol from the proximal cache at the proximal IPA to the  
3 destination cache at a destination IPA.

4  
5  
6  
7 13. (Original) The method of claim 12 wherein,

8 the originating URL identifier is selected from the group  
9 consisting of,

10 an exact URL identifier being an exact URL comprising a  
11 plurality of URL components,

12 a wildcard URL identifier being a wildcard URL comprising a  
13 plurality of URL component a last URL component of which being a  
14 wildcard component, and

15 a coded URL identifier being a coded URL comprising a series  
16 of hashing codes of a decomposed URL being a decomposition of the  
17 URL selected from the group consisting of either an exact URL or a  
18 wildcard URL each of which comprising a series of URL components,  
19 the series of hashing codes being a sequence of hashing codes of  
20 respective hashing of URL segments of a respective series of  
21 increasingly concatenated URL components or the series of URL  
22 components of the URL.

23  
24  
25  
26  
27  
28 ///

1 14. (Currently Amended) The method of claim 12 further comprising  
2 the steps of[[,]]:

3 repeating the URL identifier generating step, proximal IPA  
4 generating step, distance generating step, the associating step, a  
5 plurality of times for generating a plurality of routing items each  
6 comprising a URL identifier and a respective distance metric, and  
7 incorporating the plurality of routing items within a protocol  
8 data structure within the routing packet prior to the transmitting  
9 step, the routing protocol packet comprising the URL and a  
10 respective distance metrics and comprising the proximal IPA and the  
11 destination IPA.

12  
13 15. (Original) The method of claim 12 wherein,

14 the storing steps creates a routing table for cross referencing  
15 the plurality of URL identifiers to the plurality of distance  
16 metrics and to one or more juxtaposed cooperative web caches IPAs  
17 of one or more juxtaposed cooperative web caches of the cooperative  
18 web caches, the one or more juxtaposed cooperative web caches for  
19 routing URL identifiers to distal web caches storing the web  
20 content data of the respective plurality of URL identifiers.

21  
22 16. (Currently Amended) The method of claim 15 wherein,

23 the proximal cache and the one or more juxtaposed cooperative  
24 web caches being within a local group of cooperative web caches.

25  
26 17. (Currently Amended) The method of claim 16 wherein,

27 the proximal cache is within one or more local groups of  
28 cooperative web caches.